

PCT/EP200 4/ 0 1 2 6 3 0



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

REC'D 09 DEC 2004

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03388082.4

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

BEST AVAILABLE COPY



Anmeldung Nr:
Application no.: 03388082.4
Demande no:

Anmeldetag:
Date of filing: 01.12.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Sony Ericsson Mobile Communications AB

221 88 Lund
SUEDE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Camera

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H04N1/21

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

Camera

Technical field of the invention:

- 5 This invention relates to a camera with activation means for initiating storage of a picture in a first storage means upon activation of the activation means, which camera is arranged to furthermore store a first plurality of pictures in a second storage means upon activation of the activation means, where the camera further comprises display means for displaying pictures stored in the
10 first storage means.

Description of related art:

- 15 With prevalent cameras it is a well known problem that it can be difficult to capture the best moment for a picture or photograph. For example, persons might close their eyes in the moment the picture is taken or show a disadvantageous face. In photographing moving persons or items, such as a baseball or tennis player hitting the ball, it is difficult to photograph the exact event. To alleviate this problem, some cameras provide the possibility of
20 taking a sequence of photographs as separate pictures. An activation of an activation means, e.g. holding down a button, will trigger a sequence of pictures being taken, which is called "burst shooting". In digital cameras, unwanted pictures might thereafter be deleted.
- 25 However, it is a problem that only photographs taken *after* the button was pressed is stored; if the moment to be photographed took place just *before* the button was actually pressed, no photographs will have been taken at the desired moment. It is also a problem that the user has to manually delete every picture taken, which he/she doesn't want to keep, in that this can be
30 rather time consuming and cumbersome.

Summary of the invention:

These problems are remedied when the camera of the kind mentioned in the introductory is arranged to store a first plurality of pictures in the second storage means substantially continuously, independently of activation of the activation means, and that the camera is arranged to, upon activation of the activation means, furthermore store a second plurality of pictures in the second storage means.

Hereby, the camera provides a user with two pluralities of pictures in excess of the picture taken (and stored in the first storage means) upon activation of the activation means: a first plurality of pictures taken before the activation of the activation means and a second plurality taken after activation of the activation means. To a user, these pluralities of pictures occur as one plurality of pictures, whereof some are taken before the activation of the activation means, and others are taken thereafter, in excess of the actual picture taken at the time of activation of the activation means.

It should be noted, that term "initiating storage of a picture in a first storage means" could denote the user activated storage of a picture stored firstly in the second storage means. In this case, the camera substantially continuously stores pictures independently of activation of the activation means. When the activation means is activated, the picture taken at that instant as well the second plurality of pictures are stored in the second

storage means. Thereafter, three buttons (or directions from a multi-way joystick control means) would give the user the possibility of either a) displaying the picture(s) taken immediately before the time t_0 , b) display the picture(s) taken immediately after the time t_0 , c) confirm the currently displayed picture and initiate storage of one or more selected pictures into the first storage means.

In a preferred embodiment the first storage means of the camera according to the invention is a non-volatile storage means. Moreover, it is advantageous if the second storage means of the camera according to the invention is a temporary storage means. One preferred example of such a temporary storage means is a buffer storage. Thus, the first storage means could be a non-volatile but erasable and rewritable storage means, such as e.g. flash memory card, a memory stick, an SD card, etc., whilst the second storage means preferably is a volatile memory, such as RAM. Typically, the second storage means is a buffer means using the FIFO principle (First In First Out), such as a circular buffer. Hereby, a continuous stream of pictures can be shifted into the beginning of the buffer, when the buffer is full.

In a preferred embodiment according to the invention the camera comprises means for initiating displaying of pictures stored in the second storage means on the display means. Hereby, a user can review the pictures stored in the first storage means as well as the pictures stored in the second storage means. Preferably, the camera further comprises means for selecting a picture from the second storages means and means for storing the selected picture in the first storage means. Hereby, a user can initiate the displaying of pictures stored in the first storage means. If the user is content with the pictures stored in the first storage means, no action needs to be taken. However, if the user is discontent with the pictures in the first storage means, hen can initiate displaying of pictures stored in the second storage means. If he/she wants to keep one or more pictures stored in the second storage means, he/she selects the respective picture(s) and initiates the storing of the respective picture(s) into the first storage means. This storing typically is a copying of the picture from the second to the first storage means; however, the picture might also be deleted from the second storage means immediately after storing thereof in the first storage means. Hereby, a user experiences the possibility of going back and/or ahead in time in relation to pictures taken before/after the moment of activation of the activation means.

Preferably, the camera according to the invention comprises means for a user to set the number of pictures to be stored in the second storage means per time unit, and preferably the camera comprises means for a user to set
5 the total number of pictures in the second plurality of pictures. Hereby, the user can adjust the buffered time interval according to his/her needs or wishes. The term "the buffered time interval" is meant to denote the time interval within which pictures are stored in the second storage means. Typically, this buffered time interval is a number of milliseconds, seconds or
10 even minutes. The number of pictures which can be stored per time interval can be almost any number; however, typically between 1 and 50 pictures per second are stored in the second storage means.

Preferably, the camera comprises means for automatically adjusting the total
15 number of pictures in the second plurality of pictures in dependency of one or more of the following: resolution of pictures, shutter, hardware limits, and memory limits. Hereby, the buffer size is adjusted in accordance with the actual status of the camera. Moreover, it is preferred, that the camera comprises means for a user to set the resolution of pictures to be stored in
20 the first and/or second plurality of pictures.

In a further preferred embodiment, the camera according to the invention comprises means for a user to select a subset of pictures from the second
~~storage means to be stored in the first storage means. Thus, a sequence of~~
25 pictures can be stored in a user friendly way, i.e. with few interactions; eventually in a special file format.

Preferably, the camera according to the invention comprises a flash which is
30 activated synchronously with the taking of pictures. The flash might e.g. be synchronized with the camera shutter. Hereby, it is every picture is

accompanied with a flash, enhancing the possibility of right exposure of the pictures taken.

5 Preferably, that real time information can be stored with each picture in the second storage means of the camera according the invention has the feature. This information can be displayed together with pictures displayed on the display means of the camera so that a user can see the time at which the displayed picture(s) was (were) taken and the time elapsed between two subsequent pictures in the second storage means.

10

In yet a preferred embodiment of the camera according to the invention, the camera is integrated in a mobile communications device, e.g. a mobile telephone. Hereby, the mobile communications device can be used to send pictures taken by means of the camera to other devices comprising adequate communications means. Moreover, the display means of the camera and a display means of the communication device might be integrated into one display means.

15 In an alternative, the camera according to the invention comprises means for establishing a connection to a mobile communication device. Such means could be any cable, plug, connector or other suitable connecting means.

20 The invention moreover concerns a mobile telephone comprising a camera according to the invention. This provides similar advantages as described above.

25

Finally, the invention relates to a method of taking pictures with a camera which method comprises storing a picture in a first storage means upon activation of activation means; storing a first plurality of pictures in response to the activation of the activation means; storing, substantially continuously, a second plurality of pictures independently of activation of the activation

30

means; displaying the picture stored in the first storage means on the display means; on user demand, displaying pictures from the first plurality and/or the second plurality of pictures on the display means; providing the user with the possibility to choose a picture in the first or in the second plurality of pictures to be stored in the first storage means; and if the user chooses a picture from the first or the second plurality of pictures to be stored in the first storage means, storing the chosen picture in the first storage means.

A few more preferred embodiments are described in dependent claims.

10

Brief description of the drawings:

The invention will be described more fully below in connection with preferred embodiments and with reference to the drawings, in which:

15

Fig. 1 is a schematic diagram showing those structural elements of a camera 100 which are of relevance to the invention;

20

Fig. 2 is a schematic representation of the indexing of pictures in the buffer means;

Fig. 3 shows pictures displayed on the display means of the camera according to the invention; and

25 Fig. 4 shows a picture browser displaying one picture and an option menu shown on the display means of the camera according to the invention.

Detailed description of embodiments:

30 Fig. 1 is a schematic diagram showing those structural elements of a camera 100 which are of relevance to the invention. The camera can be a digital

camera or a camcorder. However, it is not precluded that the camera could be a traditional camera with a photographic film as the first storage means and with further storage means for temporary storage of pictures.

- 5 The term "digital camera" is meant to cover any camera which records and stores pictures, e.g. photographic images, in digital form that can be fed to a computer as the pictures are recorded or stored in the camera for later loading into a computer or printer. A digital camera has a built-in computer or (micro)processor, and records pictures in an entirely electronic form. Thus
- 10 the digital camera does not contain a photographic film. The term "traditional camera" is meant to cover any camera storing still pictures onto a photographic film. Both types of cameras can contain a series of lenses that focus light to create a picture of a scene. Whilst a traditional camera focuses this light onto a piece of film, the digital camera focuses it onto a
- 15 semiconductor device that records light electronically; hereafter the computer or (micro)processor breaks this electronic information down into digital data.

The camera 100 comprises a first storage means 101 and a second storage means 102 as shown in fig. 1. Preferably the first storage means 101 is a

20 non-volatile but erasable and rewritable storage means, such as e.g. flash memory card, whilst the second storage means 102 typically is a buffer storage means, preferably volatile memory, such as RAM.

Moreover, the camera 100 contains an activation means 130, which could be

25 a push-down button, a scrollable button, a touch screen, etc. Further, the camera contains a display 110, e.g. an LCD, for displaying i.a. pictures taken by the camera to the user and a (micro)processor 120 controlling the functions of the camera. The camera moreover comprises elements known to be necessary to make the camera work, but falling beyond the scope of this

patent application, such as viewfinder, zoom, shutter, aperture setting, CCD, ADC, etc.

As described above, the camera 100 has activation means 130 for initiating
5 storage of a picture in a first storage means 101 upon activation of the
activation means 130 and the camera 100 comprises display means 110 for
displaying pictures stored. Furthermore, the camera 100 is arranged to store
a first plurality of pictures in a second storage means 102 upon activation of
the activation means 130, and the camera is arranged to further store a
10 second plurality of pictures in the second means 102 substantially
continuously, independently of activation of the activation means 130. This
means, that whenever the camera is turned on so that the view finder is
active, pictures are stored in the second storage means 102 as a first
plurality of pictures. When the activation means is activated, a second
15 plurality of pictures are stored in addition to the first plurality, so that a
number of pictures taken before and after the activation of the activation
means are kept in the second storage means.

Moreover, the camera comprises means (not shown) for initiating displaying
20 of pictures from the first or second plurality of pictures, i.e. from the second
storage means, on the display means of the camera and means for selecting
a picture from the second storage means as well as means for storing the
selected picture in the first storage means. Hereby, a user can navigate
through the pluralities of pictures taken before and after activation of the
25 activation means and select one or more pictures to be stored in the first
storage means.

A user can experience an operation of the camera 100 as follows: when
he/she turns on the camera so that the view finder is active, e.g. by activating
30 a button to activate the functions of the camera, the camera 100 begins

storing a certain number of pictures with full resolution in a buffer memory, i.e. the second storage means 102. This preferably is a circular buffer memory, so that whenever the buffer memory is full, the oldest pictures are substituted in the memory by recent pictures. By substituting pictures in the
5 buffer memory by newer pictures, excessive filling of the storage means can be avoided. Whenever the user activates the activation means 130, e.g. presses a shutter release button, a picture is taken and stored in the first storage means 101. This picture can be shown to the user on the display 110 of the camera 100, either automatically or by user demand. Such a user
10 demand typically would be an activation of a button or a touch screen. If the user is content with the picture, he/she shouldn't need to do anything; however, the camera might prompt the user to indicate acceptance of the picture or a menu could be displayed on the display 110 with the possibility of entering a mode of reviewing pictures stored in the second storage means
15 102

However, the camera could also be arranged so that a user, if he/she is discontent with the picture taken at the moment of activation of the activation means, i.e. the picture stored in the first storage means, should prompt; e.g.
20 by pressing a button of the camera 100, the displaying of pictures from the first plurality and/or the second plurality of pictures on the display means 110. Subsequently, pictures from the first and/or second plurality is displayed on the display means 110 of the camera 100 and the user is provided with the possibility to choose a picture in the first or in the second plurality of pictures
25 to be stored in the first storage means. If the user chooses a picture from the first or the second plurality of pictures to be stored in the first storage means, the camera performs the storing of the chosen picture in the first storage means. Typically, the user might only want one picture of the situation, he/she has photographed, but naturally it is preferred that he/she can copy or
30 transfer more than one picture from the second means into the first storage means.

Thus, one of the merits of the invention is that the user experiences a possible "going back in time" in relation to the moment of activation of the activation means: pictures from before (as well as after) the moment of
5 activation of the activation means are stored in the camera and can be shown to the user and be kept.

The camera has connection means and/or transmission means (not shown) arranged to transfer the pictures stored in the first storage means 101 to a
10 computer, a computer server or a printer to facilitate printing out of the pictures, transferral to other computers or computer servers via a computer network such as the Internet, transmitting the pictures over a mobile phone network or WLAN, LAN, etc.

15 It should be noted, that the term "substantially continuously" is meant to denote "at short time intervals". Such short time intervals could possibly, but not necessarily, be predefined time intervals. The term is meant to cover intervals of a few seconds or less, preferably such that between one and 100 pictures are taken every second. However, the camera can be arranged to let
20 a user to set the number of pictures to be stored in the second storage means per time unit. The extreme points of the user programmed number of pictures to be stored per time unit would normally be 100 pictures per second and one picture every 10 seconds.

25 The means for initiating displaying (not shown) of pictures on the display of the camera could be a button or a touch screen. The means for letting the user select a picture to be stored could be one or more of the following: a menu shown on the display 110 of the camera 100; displaying pictures on the display 110; a user interface (not shown); means for transferring/copying
30 pictures chosen from the second to the first storage means.

The above description of an embodiment of the invention has been directed to a digital camera; however, as already mentioned, the invention could also be directed to a traditional camera containing a photographic medium, i.e. a film, and comprising further storage means for intermediate storing of pictures taken before and after activation of the activation means. In this case, the camera could be arranged to store a picture at the moment of activation of the activation means in an electronic form to be displayed to the user plus a first plurality of pictures taken after the activation of the activation means and a second plurality of pictures taken before said activation. If the user is not content with the picture taken at the moment of said activation, he/she can access the further pictures in the first and second plurality of pictures. If the user prefers one or more of the pictures in the first and/or second plurality of pictures, he/she can choose to save this picture and get it transferred to the first storage means of the camera, being the photographic film. However, this would require a conversion of information stored in the storage means for intermediate storing of pictures to light information required to be stored in the photographic medium.

Fig. 2 is a schematic representation of the indexing of pictures in the buffer means 102 (fig. 1). The squares 140, 150, 160 indicate the pictures taken before the time of activation of the activation means, at the time of activation of the activation means and after the time of activation of the activation means, respectively. t_0 , t_5 , t_3 , t_2 , etc. denotes instances at which a picture is stored in the second storage means, i.e. the buffer means. The instance t_0 indicates the time of activation of the activation means. The squares 140 to the left of the square 150 represent pictures taken before the activation of the activation means, and the squares 160 to the right of the square 150. When the indexing of the pictures in the second storage means is as shown in fig. 2, user navigation between the pictures can be arranged so that firstly the picture 150 taken at the time of activation of the activation means is displayed. If the user wants more pictures to be displayed he/she can push a

button to view the picture taken just before 140; by repeated pushes of the button the older pictures are displayed. By pushing another button (or another part of the same button), pictures taken after the picture 140 can be displayed, so that the pictures closest in time to the picture 140 is shown first.

- 5 This function of the camera can be organized in a number of ways and the buttons of the camera arranged to navigation through the pictures can be any kind of known buttons or joysticks or corresponding control means.

- 10 In fig. 2 the picture taken at t_0 is stored in the buffer means 102 (fig. 1). In this instance, the picture taken at t_0 is not necessarily stored in the first storage means. Thus, when the picture is taken at t_0 , it can be displayed from the second storage means. Three buttons (or directions from a multi-way joystick control means) would give the user the possibility of either a) displaying the picture(s) taken immediately before the time t_0 , b) display the picture(s) taken
15 immediately after the time t_0 , c) confirm the currently displayed picture and initiate storage of one or more selected pictures into the first storage means.

- In an alternative (not shown) the picture taken at the time of activation of the activation means, i.e. t_0 , might be stored in the first storage means only. Thus
20 the second storage means would only contain pictures taken before and after the activation of the activation means. This is however not important to the function of the camera and the navigation through the pictures is as explained above.

-
- 25 In case the buffer means is a circular buffer, the buffer could for example have space for 50 pictures with indices 0 to 49. The camera would have an index counter and continuously store pictures to the space with the index indicated by the actual value of the counter. After that the index counter is incremented by one. After reaching the full buffer, i.e. "49", the index counter
30 is set back to "0". After activation of the activation means, the value of the counter at the instance of the activation of the activation means would be

transferred to a buffer register. The camera would continue to store for instance 25 more pictures after the activation of the activation means, so that the circular buffer contains 25 pictures from before and 25 pictures from after the activation of the activation means, whereof the pictures taken before the
 5 activation of the activation means correspond to the first plurality of pictures and the pictures taken after said activation correspond to the second plurality of pictures. The number of pictures in the first and second pluralities need not be equal. The counter value in the buffer register would contain the information of which indices correspond to which pictures as well as where
 10 the boundary in the circular buffer between pictures taken before and after activation of the activation means is to be found.

It should be noted, that the camera should be arranged to keep track of the moments of activation of activation means to account for successive
 15 activations of the activation means being performed quickly one after another. This is a task of keeping track of which pictures are stored at which moments and keeping the pictures in the second storage means for a certain amount of time, sufficient to facilitate a review by the user.

20 Fig. 3 shows pictures 200 displayed on the display means 110 of the camera 100 according to the invention. In fig. 3 four pictures 201, 202, 203, 204 are shown. The pictures 201, 202, 203, 204 are portrait pictures of a person with four different facial expressions. The number of pictures displayed is only exemplary and can be varied according to the size and shape of the display
 25 means 110. The pictures 200 displayed could be pictures from the first plurality of pictures (i.e. taken after activation of the activation means) or from the second plurality of pictures (i.e. taken before activation of the activation means), where both pluralities of pictures are stored in the second storage means. Preferably, it should be possible to display the pictures from the first
 30 and second storage means in their natural order of succession. An indication of the moment of activation of the activation means could also be given, e.g.

by different colouring of the frames around the pictures, an indicator such as a symbol, e.g. an arrow, "+", "-", etc., or by including the picture taken at the actual moment of activation of the activation means in a highlighted frame. The user should be able to scroll in the pictures stored in the storage means
5 101, 102, 103 and see the pictures in their true temporal order of succession.

Fig. 4 shows a picture browser displaying one picture 210 and a picture and an option menu 211 shown on the display means 110 of the camera according to the invention. The layout and content of the option menu 211 is
10 given as a non-limited example only; the option menu can be designed to any appropriate user needs. The option menu 211 contains a head line "Options:" 201 and three lines containing options, viz. "Change capture moment", "Properties", "Delete". These options could be supplemented and/or changed according to the demands to the picture browser. In fig. 4 a frame 212 is
15 shown around the option "Change capture moment", indicating that a user wants to enter this functionality of the camera. According to the invention, if the user activates the option "Change capture moment" 201, an array of pictures, e.g. as shown in fig. 3, is presented to the user and he/she can select the picture he/she prefers. Thus the user can select pictures of what
20 has happened before he/she has pressed the shutter release button of the camera.

As mentioned above, the camera according to the invention can be
~~integrated into a mobile communications device or comprise means for~~
25 establishing a connection to a mobile communications device. Normally, a mobile communication device contains a display means and in the case of the camera being integrated into a mobile communication device, the display of the mobile communication device and the camera can be shared. Moreover, the mobile communication device can send pictures taken by the
30 camera according to the invention to other devices containing communication means.

Claims:

1. A camera (100) with activation means (130) for initiating storage of a picture in a first storage means (101) upon activation of the activation means (130), where the camera (100) further comprises display means (110) for displaying pictures stored in the first storage means (101), **characterized in** that the camera (100) is arranged to store a first plurality of pictures in the second storage means (102) substantially continuously, independently of activation of the activation means (130), and that the camera (100) is arranged to, upon activation of the activation means, furthermore store a second plurality of pictures in the second storage means (102).
2. A camera (100) according to claim 1, **characterized in** that the first storage means is a non-volatile storage means.
3. A camera (100) according to claim 1 or 2, **characterized in** that the second storage means (103) is a temporary storage means.
4. A camera (100) according to claim 3, **characterized in** that the temporary storage means is a buffer storage.
5. A camera (100) according to any of the claims 1 to 4, **characterized in** that the camera (100) comprises means for initiating displaying of pictures stored in the second storage means (102) on the display means (110).
6. A camera (100) according to any of the claims 1 to 5, **characterized in** that the camera (100) further comprises means for selecting a picture from the second storages means (102) and means for storing the selected picture in the first storage means (101).

7. A camera (100) according to any of the claims 1 to 6, **characterized in** comprising means for a user to set the number of pictures to be stored in the second storage (102) means per time unit.

5 8. A camera (100) according to any of the claims 1 to 7, **characterized in** comprising means for a user to set the total number of pictures in the second plurality of pictures.

10 9. A camera (100) according to any of the claims 1 to 7, **characterized in** comprising means for automatically adjusting the total number of pictures in the second plurality of pictures in dependency of one or more of the following: resolution of pictures, shutter, hardware limits, and memory limits.

15 10. A camera (100) according to any of the claims 1 to 9, **characterized in** comprising means for a user to set the resolution of pictures to be stored in the first and/or second plurality of pictures.

20 11. A camera (100) according to any of the claims 1 to 10, **characterized in** that the number of pictures in the second plurality of pictures preferably lies between 1 and 500, more preferably between 2 and 250, and most preferably between 2 and 50.

25 12. A camera (100) according to any of the claims 1 to 11, **characterized in** comprising means for a user to select a subset of pictures from the second storage means (102) to be stored in the first storage means (101).

13. A camera (100) according to any of the claims 1 to 12, **characterized in** that a flash of the camera is activated synchronously with the taking of pictures.

14. A camera (100) according to any of the claims 1 to 13, **characterized in** that real time information is stored with each picture in the second storage means.
- 5 15. A camera (100) according to any of the claims 1 to 14, **characterized in** that the camera (100) is integrated in a mobile communications device.
16. A camera (100) according to any of the claims 1 to 15, **characterized in** that the camera (100) comprises means for establishing a connection to a
10 mobile communications device.
17. A mobile telephone comprising a camera (100) according to any of the claims 1 to 16.
- 15 18. A method of taking pictures with a camera (100) which method comprises:
- storing a picture in a first storage means (101) upon activation of activation
means (130);
20 storing a first plurality of pictures in response to the activation of the activation means (130);
- storing, substantially continuously, a second plurality of pictures
25 independently of activation of the activation means (130);
- displaying the picture stored in the first storage means (101) on the display
means (110);
- 30 on user demand, displaying pictures from the first plurality and/or the second plurality of pictures on the display means (110);

providing the user with the possibility to choose a picture in the first or in the second plurality of pictures to be stored in the first storage means (101); and

- 5 if the user chooses a picture from the first or the second plurality of pictures to be stored in the first storage means (101), storing the chosen picture in the first storage means (101).
-

ABSTRACT:

A camera (100) with the functionality of taking a picture at the instant of activating a shutter release button as well as a plurality of pictures which is stored in a buffer storage. The plurality of pictures contains pictures taken before as well as after the traditionally taken picture. This provides the user with the possibility of reviewing the pictures taken at the instant of activation of the shutter release button as well as the pictures in the plurality of pictures and selecting one or more preferred pictures to be stored in a non-volatile memory of the camera.

(fig. 1 should be published).

1/2




Fig. 1




Fig. 2




Fig. 3




Fig. 4

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.